

1/8" HWS

ROTIERENDE TANKREINIGUNGSDÜSE ROTATING TANK CLEANING NOZZLE

AUSFÜHRUNG

- Rotierende Tankreinigungsdüse mit 1/8"-Innengewinde (ISO 228)
- Anschweiß- und Clip-On Version auf Anfrage
- CIP-fähig
- ATEX auf Anfrage

SPRÜHEIGENSCHAFTEN

- 360° rotierend
 - andere Strahlwinkel auf Anfrage
- Angetrieben durch das Reinigungsmedium
- Drehzahl druckabhängig
- Selbstreinigend
- Max. Behälterdurchmesser: 1000 mm

WERKSTOFFE

- Düsenkörper: 1.4404 (316L SS)
 - andere auf Anfrage (z.B.: 2.4610, 1.4435, etc.)
- Laufkugeln: 1.4401 (316 SS)
 - andere auf Anfrage (z.B.: 2.4610, 1.4435, etc.)

DESIGN FEATURES

- Rotating tank-cleaning nozzle with 1/8"-female thread (ISO 228)
- Weld- and Clip-On connections on request
- CIP-able
- ATEX on request

SPRAY CHARACTERISTICS

- 360° rotating
 - other spray angles on request
- Driven by the cleaning fluid
- Rotation speed is pressure-dependent
- Self-Cleaning
- Maximum Tank-Diameter: 1000 mm

MATERIALS

- Nozzle: 1.4404 (316L SS)
 - other materials on request (e.g.: 2.4610, 1.4435, etc.)
- Balls: 1.4401 (316 SS)
 - other materials on request (e.g.: 2.4610, 1.4435, etc.)



Optimaler Arbeitsdruck
Recommended Operating Pressure

